

Excelon®

# Excelprene TPE Food Process Tubing



## APPLICATIONS:

FOOD PUMP TUBING

DAIRY PUMP TUBING

PERISTALTIC PUMPS

RUBBER REPLACEMENT TUBING

COSMETIC PRODUCTION

CHEMICAL TRANSFER

HOT BEVERAGE DISPENSING

# High-Performance Tubing for Food & Dairy Processing

- Alternative to Tygon® A-60-F
- Preferred choice over traditional rubber tubing
- Withstands extreme temperatures from -75°F to 275°F
- Compatible with most sanitizers and cleaners
- Chemically compatible with a wide range of fluids
- Meets FDA criteria
- Batch consistency

**Excelprene TPE Food Process Tubing** is a high-performance tubing formulated to withstand the extreme temperatures frequently experienced during food, dairy, and cosmetic processing applications. Extremely flexible, it resists kinks and retains its shape while installing quickly and easily. Excelprene is durable with excellent fatigue and abrasion resistance, making it an excellent choice for use in the peristaltic pumps often found in dispensing equipment. Excelprene will not crack or deteriorate following extended exposure to heat or ozone, making it the preferred choice when compared to traditional rubber tubing products.

Excelprene TPE Food Process Tubing makes cleaning and sterilization easy, as it exhibits excellent chemical resistance compared to general purpose rubber tubing and is compatible with the most harsh commercial cleaners and sanitizers. Excelprene also provides excellent acid and alkali resistance as well as good resistance to animal and vegetable oils.

## PHYSICAL PROPERTIES

PROPERTIES	
Hardness , Shore A, 15 sec, 73 degree F	69
Specific Gravity	.97
Tensile Strength	957 psi
Elongation at Break	490%
Max. Operating Temp.	275°F
Brittle Temperature	-76°F

*Values listed are typical and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.*

Samples available upon request.

Custom sizes and lengths available upon request.

**REGULATORY COMPLIANCE:** REACH, RoHS, FDA, and Prop 65 compliant.

Excelon®

# Excelprene TPE Food Process Tubing



## APPLICATIONS:

FOOD PUMP TUBING  
DAIRY PUMP TUBING  
PERISTALTIC PUMPS  
RUBBER REPLACEMENT TUBING  
COSMETIC PRODUCTION  
CHEMICAL TRANSFER  
HOT BEVERAGE DISPENSING

## EXCELPRENE TPE FOOD PROCESS TUBING SIZING CHART

ITEM NO.	ID	OD	WALL	LENGTH	MINIMUM BEND RADIUS	MAX. WKG PRESSURE PSI @ 73°F
900105F	.062	.187	.062	50' Coil	.250	34
900205F	.125	.250	.062	50' Coil	.500	19
900305F	.187	.312	.062	50' Coil	.750	13
900605F	.250	.375	.062	50' Coil	1.250	10
900805F	.250	.500	.125	50' Coil	.750	19
900905F	.312	.437	.062	50' Coil	1.500	8
901205F	.375	.500	.062	50' Coil	2.250	7
901405F	.375	.625	.125	50' Coil	1.250	13
902005F	.500	.750	.125	50' Coil	2	10
902605F	.625	.875	.125	50' Coil	3.250	8
903105F	.750	1	.125	50' Coil	4	7

*Values listed are typical and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.*



21649 Cedar Creek Ave  
Georgetown, DE 19947  
P: 302-855-0139  
E: [tpisales@excelon.com](mailto:tpisales@excelon.com)  
[www.thermoplasticprocesses.com](http://www.thermoplasticprocesses.com)

All contents © 2025 Thermoplastic Processes

## LIABILITY CLAUSE

TPI PARTNERS, INC., hereinafter called the "Manufacturer," warrants that its products shall be free from defects in workmanship and materials.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES FOR FITNESS FOR PURPOSE INTENDED. The Manufacturer's liability is limited to the replacement of any materials which, after an examination by the Manufacturer and its sole option, are found to be defective. The Manufacturer will honor only those claims which are presented within ninety (90) days of the delivery of the materials to the purchaser. THE MANUFACTURER SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR CONSEQUENTIAL DAMAGES. This literature supersedes all previous literature and the responsibilities made thereon. CAB-1/02

Samples available upon request.

Custom sizes and lengths available upon request.

**REGULATORY COMPLIANCE:** REACH, RoHS, FDA, and Prop 65 compliant.