Excelon® Welding Rod



APPLICATIONS: TANK BUILDERS OUTDOOR FURNITURE PLAYGROUND EQUIPMENT **CLEAN ROOM BUILDING**

Welding Rod

- · Available in a large variety of materials
- Dimensions from .090" OD to .500" OD
- · Variety of shapes

- Metric sizes also available
- · Offered on 30LB wooden reels

The most important element to successful thermoplastic welding is the filler rod. To insure proper bonding, it is essential that filler rods be made with the same high grade resins used in the material being welded.

Our rod is extruded using only the highest grade resins available.

AVAILABLE MATERIALS

- ABS
- Pipe Grade HDPE
- Corzan

• PVC

• Styrene

• Corzan White 4910

• LDPE

PETG

• Urethane I & II

LLDPE

CPVC

Kynar

DIMENSIONS

- .125
- .156
- .187
- .250
- .375
- .312
- .500

SHAPES

- MW
- MWK
- LEISTER
- KST
- OVALS

Custom colors, shapes, and sizes available upon request.

REGULATORY COMPLIANCE FOR STOCK PIPE GRADE HDPE: REACH, RoHS, and Prop 65 compliant



21649 Cedar Creek Ave Georgetown, DE 19947 P: 302-855-0139 E: tpisales@excelon.com www.thermoplasticprocesses.com

All contents © 2025 Thermoplastic Processes

LIABILITY CLAUSE

TPI PARTNERS, INC., hereinafter called the "Manufacturer," warrants that its products shall be free from defects in workmanship and materials.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES FOR FITNESS FOR PURPOSE INTENDED. The Manufacturer's liability is limited to the replacement of any materials which, after an examination by the Manufacturer and its sole option, are found to be defective. The Manufacturer will honor only those claims which are presented within ninety (90) days of the delivery of the materials to the purchaser. THE MANUFACTURER SPECIFICALLY DISCLAIMS ANY AND ALL LIABILITY FOR CONSEQUENTIAL DAMAGES. This literature supersedes all previous literature and the responsibilities made thereon. CAB-1/02